


CAS-1000-I2C/E™

CORELIS
An EWA Company

Advanced I²C and SMBus Analyzer, Exerciser, Emulator, and Programmer

Preferred Bus Analysis Solutions—Acclaimed Technical Support



Features

- Supports I²C and SMBus monitoring and traffic generation for Standard-mode, Fast-mode, Fast-Mode Plus (Fm+) with I²C bus data rates up to 5 Mbit/s
- Supports High-Speed mode (Hs-mode) monitoring
- Simultaneous monitoring and emulation—up to 1 emulated master and 10 emulated slaves, all running concurrently
- Measures common I²C bus electrical and timing parameters, complete with a graphical waveform display
- Injects glitch and signal patterns, protocol errors, and slave clock stretching to override the bus and stress the UUT
- Programmable bus voltage reference and software configurable pull-up resistors on the SDA and SCL lines
- Powerful command and script language for emulation control and automated testing
- Passive traffic monitoring with state and timing recording
- Unlimited and continuous logging of transaction data to file
- Time stamping, message filtering, and symbolic translating
- Programmable trigger event to highlight and display bus transactions of interest
- In-System Programming of I²C serial EEPROMs
- High-speed, bus-powered USB 2.0 interface
- I2C Exerciser software supports Windows® XP, Windows Vista®, and Windows 7 operating systems

While the I²C interface seems simple on the surface, this straightforward architecture is not immune to intermittent glitches, device misbehaviors, and protocol violations. Tracking down these errors can be tedious business if the right tool is not utilized.

The CAS-1000-I2C/E bus analyzer is a bloodhound when it comes to sniffing out I²C irregularities. The ability to spot complex problems and identify invisible obstacles make it the preferred I²C development solution. Advanced logging, debugging, emulation, and verification capabilities offer power and versatility, yet the Windows-based user interface makes the most complex features simple to use.

The CAS-1000-I2C/E succeeds where simple monitoring and interactive I/O tools fall short—a complete solution to monitoring, emulating, stressing, and characterizing I²C and SMBus interfaces.

Benefits


- Monitor displays high-level view of I²C bus traffic. Bit and protocol level information is also available and graphically displayed as a timing waveform.
- Debugger, Emulator, and Test Script functions provide direct read/write access on the I²C bus. The CAS-1000-I2C/E acts as a master to generate or a slave to respond to I²C transactions while simultaneously monitoring the traffic on the bus.
- I2C Exerciser software is easy to learn and use. The graphical interface allows quick access to powerful functionality and filters out the noise, so you focus on the trace data that you actually need to see.
- Parameters Scope enables fast, automatic measurement and verification of common target bus electrical and timing parameters.

Applications


- **Software Development** - Monitor and log I²C bus traffic in real-time
- **Hardware Debugging** - Generate traffic to exercise the bus and communicate with its peripheral components
- **Factory Test** - Create automated test sequences, including bus electrical and timing measurement

Learn More: For more information about Corelis products, please visit www.corelis.com


The CAS-1000-I2C/E is an advanced, feature-packed and powerful I²C debugging and analysis system. By providing full visibility as well as detailed control of the I²C bus, the CAS-1000-I2C/E enables engineers to save time and resources, replacing multiple instruments with a single intuitive and specialized tool. The Corelis hardware and software provide a convenient easy to use environment for hardware debugging, software development, bus validation, and in-system programming.



Parameters Scope: Measure and display common I²C Bus electrical and timing parameters.



I2C Exerciser Monitor: Log, analyze, and display trace and timing data.



Glitch Pattern Editor: Create and inject customized digital patterns to stress I²C buses.

The CAS-1000-I2C/E leaves standard serial bus analyzers behind by providing a complete, peerless set of tools to generate bus traffic, inject glitches and protocol errors, measure bus electrical and timing parameters, program serial EEPROMs, emulate I²C masters and slaves, and more—all while simultaneously monitoring the bus, logging trace and timing data, and verifying I²C bus behavior on the fly. The I2C Exerciser software interface, included with the CAS-1000-I2C/E, provides a consolidated and intuitive GUI (Graphical User Interface) for host PC control and visualization of all bus monitoring and traffic generation features.

Hardware Specifications

General

Mechanical Dimensions	5.48 x 1.00 x 4.66 (+/- 0.25) inches
Shipping Weight	7 pounds (approximate)
Certifications	RoHS Compliant , CE Marked

USB Interface

USB Transfer Rate	High-speed USB 2.0
USB Cable	Ships with a 6 foot USB 2.0 A to B cable

I²C Interface

I ² C Bus Connector	RJ45 (AMP P/N 406549-1)
I ² C Bus Cable	Ships with a 12 inch interface cable that terminates in flying leads suitable for connection to 0.025" square posts. Test clips are included.

Ordering Information

Part Number - 90002

- For more information, or to order this product online, please visit our website at: <http://www.corelis.com/CAS-1000>
- View the CAS-1000-I2C/E whitepaper at: <http://www.corelis.com/whitepapers/>

CORELIS

13100 Alondra Blvd.
Cerritos, CA 90703, USA
Phone: +1 888-808-2380 (US & Canada)
Phone: +1 562-926-6727 (International)
Fax: +1 562-404-6196
www.corelis.com